



PSTF3 750 Submersible Pump

Durable, lightweight and perfect for any job

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

| | |
|----------------------|-------------|
| Flow rate max. | 230.0 l/min |
| Solid diameter max. | 7.0 mm |
| Delivery height max. | 19.0 m |

■ Mechanical Details

| | |
|------------------------------|----------|
| Length | 317.0 mm |
| Width | 185.0 mm |
| Height | 388.0 mm |
| Operating weight | 19.0 kg |
| Intake-/Pressure socket-dia. | 80.0 mm |

■ Motor

| | |
|-----------------|---------|
| Nominal power | 0.75 KW |
| Nominal current | 10.0 A |
| Nominal voltage | 110.0 V |

| | |
|-------------------|---------------|
| Nominal frequency | 60.0 Hz |
| Nominal speed | 3,408.0 1/min |

■ Environment Data

| | |
|-----------------------------------|---------|
| Temperature limit borrowed liquid | 40.0 °C |
|-----------------------------------|---------|

■ Electrical System

| | |
|---------------------|---------------------|
| Length Cable | 10.0 m |
| Cable cross-section | 2.0 mm ² |
| Cable definition | PVC Sheath |

■ Shipping and Storage

| | |
|---------------------|----------|
| Length for shipping | 483.0 mm |
| Width for shipping | 330.0 mm |
| Height for shipping | 260.0 mm |
| Shipping weight | 21.9 kg |