

PS2-800

Submersible Pump

Heavy-duty and durable for demanding dewatering tasks

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Variety of models
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Safe to run dry

Technical Data

Electrical - Output Details

Nominal current	4.50 A
Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Phase	1.0 ~

Mechanical - Output Details

Flow rate max.	320.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	15.0 m

Mechanical Details

Length	187.0 mm
Width	187.0 mm
Height	341.0 mm
Operating weight	13.1 kg
Intake-/Pressure socket-dia.	50.0 mm

Motor

Nominal frequency	50.0 Hz
Nominal speed	2,730.0 1/min

Electrical System

Length Cable	10.0 m
Cable cross-section	1.0 mm²

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com