



**WACKER  
NEUSON**  
*all it takes!*

## AS60e

### Electric rammers

Emission-free - For all classic rammer work

With the battery tamper, the operator works completely free of emissions. The battery-powered rammer is not only an asset when compacting soil in trenches and city centres, but also relieves the operator and the environment on every construction site. One battery charge is sufficient to do all the work of an average working day. The battery can be changed without tools in just a few easy steps and can be used for a wide range of other Wacker Neuson construction equipment.

### Highlights

- Low energy costs
- No exhaust emissions
- Maintenance-free electric motor
- Starts with a push of a button
- One battery for all products

### Technical Data

#### ■ Electrical - Output Details

|                   |         |
|-------------------|---------|
| Nominal current   | 44.00 A |
| Nominal voltage   | 51.0 V  |
| Nominal power [P] | 2.24 KW |

#### ■ Mechanical - Output Details

|                 |                            |
|-----------------|----------------------------|
| Number of blows | 680.0 1/min                |
| Area capacity   | 1,872.9 ft <sup>2</sup> /h |
| Forward Running | 0.6 fps                    |
| Power of impact | 3,821.8 lbf                |

#### ■ Mechanical Details

|                     |           |
|---------------------|-----------|
| Length              | 24.0 "    |
| Length Ramming Shoe | 13.4 "    |
| Width               | 14.3 "    |
| Width Ramming Shoe  | 11.0 "    |
| Height              | 41.3 "    |
| Weight              | 135.58 lb |

|                  |          |
|------------------|----------|
| Operating weight | 156.5 lb |
| Stroke at tamper | 2.0 "    |

#### ■ Motor

|            |                    |
|------------|--------------------|
| Motor type | Asynchronous motor |
|------------|--------------------|

#### ■ Environment Data

|                               |                        |
|-------------------------------|------------------------|
| Degree of protection          | IP23D                  |
| Storage temperature range     | -22 - 122 °F           |
| Operating temperature range   | 32 - 113 °F            |
| Sound power LWA, guaranteed   | 108.0 dB(A)            |
| Sound power LWA (Standard)    | EN 500-4               |
| HAV summation (average value) | 31.2 ft/s <sup>2</sup> |
| HAV summation (Standard)      | EN 500-4               |

#### ■ Operating Fluids

|                      |              |
|----------------------|--------------|
| Oil specification    | SAE 10W-40   |
| Oil volume           | 0.185 gal US |
| Lubrication interval | 250.0 h      |