



PSTF3 750

Submersible Pump

Durable, lightweight and perfect for any job

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	60.8 gal/mi
Solid diameter max.	0.3 "
Delivery height max.	62.3 Foot

Nominal frequency 60.0 Hz

Nominal speed 3,408.0 1/min

■ Mechanical Details

Length	12.5 "
Width	7.3 "
Height	15.3 "
Operating weight	41.9 lb
Intake-/Pressure socket-dia.	3.1 "

■ Environment Data

Temperature limit borrowed liquid 104.0 - 32.0 °F

■ Motor

Nominal power	0.75 KW
Nominal current	10.0 A
Nominal voltage	110.0 V

■ Electrical System

Length Cable	32.8 Foot
Cable cross-section	0.0 Inch ²
Cable definition	PVC Sheath

■ Shipping and Storage

Length for shipping	19.0 "
Width for shipping	13.0 "
Height for shipping	10.2 "
Shipping weight	48.3 lb