



## PG2A Dewatering Pump

Efficiently extract clear water

With its self-priming centrifugal pumping action and overall compact size, the pump is ideal for the contractor with the need for temporary water removal.

### Highlights

- Pump out vanes on back of impeller.
- Cast iron impeller and volute for long life and minimal service
- Carbon ceramic mechanical seal

### Technical Data

#### ■ Mechanical - Output Details

Flow rate max.	639.0 l/min
Solid diameter max.	6.5 mm
Suction head max.	7.6 m
Delivery height max.	27.0 m

#### ■ Mechanical Details

Length	480.0 mm
Width	375.0 mm
Height	395.0 mm
Operating weight	25.0 kg
Intake-/Pressure socket-dia.	50.0 mm

#### ■ Engine

Cooling	air cooling
---------	-------------

Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1.0
Cylinder capacity	118.0 cm <sup>3</sup>
Fuel	Gasoline
Fuel consumption	1.3 L/hr
Tank capacity	2.5 l
Oil filling max.	0.6 l
Power rating max.	2.6 KW
Engine speed (Power max.)	3,600.0 1/min
Standard (Operating power)	SAE J1349
Engine Manufacturer	Honda
Running time at 100%	1.9 hrs