

PG2A

Dewatering Pump

Efficiently extract clear water

With its self-priming centrifugal pumping action and overall compact size, the pump is ideal for the contractor with the need for temporary water removal.

Highlights

- Pump out vanes on back of impeller.
- Cast iron impeller and volute for long life and minimal service
- Carbon ceramic mechanical seal

Technical Data

Mechanical - Output Details

Flow rate max.	639.0 l/min
Solid diameter max.	6.5 mm
Suction head max.	7.6 m
Delivery height max.	27.0 m

Mechanical Details

Length	480.0 mm
Width	375.0 mm
Height	395.0 mm
Operating weight	25.0 kg
Intake-/Pressure socket-dia.	50.0 mm

Engine

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1.0
Cylinder capacity	118.0 cm³
Kraftstofftyp	Gasoline
Fuel consumption	1.3 l/h
Tank capacity	2.5 l
Oil filling max.	0.6 l
Power rating max.	2.6 kW
Engine speed (Power max.)	3,600.0 1/min
Standard (Operating power)	SAE J1349
Engine Manufacturer	Honda
Running time at 100%	1.9 hrs

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com