



AR26/3/230w

External vibrator

The expert for bulk material

Wacker Neuson external vibrators deliver excellent results when filling, consolidating, transporting and sifting bulk material. Its maximum 3,000 rpm ensures that bulk material is moving continuously, does not clump and is thus optimally prepared for later use. There are a variety of sizes and versions of Wacker Neuson external vibrators for loosening, separating and transporting.

Highlights

- Asynchronous motor with stable speed
- Adjustable eccentric weight discs

Technical Data

■ Electrical - Output Details

Nominal current	1.75 A
Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Nominal power [P]	0.40 KW
Phase	1.0 ~

Weight 6.41 kg

Unbalanced mass/side pos1 25.0
Unbalanced mass/side pos2 2.0

■ Motor

Motor type Asynchronous motor

■ Environment Data

Protection class I / Protective earthing
Degree of protection IP65

■ Electrical System

Breaker Switch On/Off no
Operating indicator No
Adjusting frequency No
Integrated transformer No
Length Cable 5.0 m

■ Mechanical - Output Details

Centrifugal force	3 kN
Vibrations	3,000.0 1/min
Vibrations (Hz)	50.0 Hz
Centrifugal force max.	2.93 kN

Weight 6.41 kg

Unbalanced mass/side pos1 25.0
Unbalanced mass/side pos2 2.0

■ Mechanical Details

Length	274.0 mm
Width	190.0 mm
Height	102.0 mm

Weight 6.41 kg

Unbalanced mass/side pos1 25.0
Unbalanced mass/side pos2 2.0