



## PST2 400 Submersible Pump

Durable, lightweight and perfect for any job

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

### Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

### Technical Data

#### ■ Mechanical - Output Details

Flow rate max.	200.0 l/min
Solid diameter max.	7.0 mm
Delivery height max.	12.0 m

#### ■ Mechanical Details

Length	250.0 mm
Width	185.0 mm
Height	328.0 mm
Operating weight	11.3 kg
Intake-/Pressure socket-dia.	50.0 mm

#### ■ Motor

Nominal power	0.40 KW
Nominal current	5.4 A
Nominal voltage	110.0 V

Nominal frequency	60.0 Hz
Nominal speed	3,350.0 1/min

#### ■ Environment Data

Temperature limit borrowed liquid	40.0 °C
-----------------------------------	---------

#### ■ Electrical System

Length Cable	6.0 m
Cable cross-section	1.3 mm <sup>2</sup>
Cable definition	PVC Sheath

#### ■ Shipping and Storage

Length for shipping	410.0 mm
Width for shipping	255.0 mm
Height for shipping	217.0 mm
Shipping weight	13.2 kg