

AR64/1,5/400

External vibrators for consolidation of prefabricated concrete factories

The experts for bulk goods

The AR54 and AR64 show their strengths particularly in continuous use: They offer vibration-proof and heat-resistant electric motor windings, highly resilient special bearings and maximum operational reliability. Even under the toughest operating conditions. The best thing about it: Their minimal maintenance requirements and long service life. Full professionals in the precast plant.

MAT: 5100004207

Highlights

- Sturdy design

Technical Data

Electrical - Output Details

Nominal current	1.40 A
Nominal voltage	400.0 V
Nominal frequency	50.0 Hz
Nominal power [P]	0.80 kW
Phase	3.0 ~

Mechanical - Output Details

Centrifugal force	4 kN
Vibrations	1,500.0 1/min
Vibrations (Hz)	25.0 Hz
Centrifugal force max.	5.05 kN

Mechanical Details

Length	352.0 mm
Width	155.0 mm
Height	188.0 mm
Weight	21.00 kg
Unbalanced mass/side pos1	29.0
Unbalanced mass/side pos2	5.0
Hole pattern length	120.0 mm
Hole pattern width	120.0 mm
Hole pattern hole diameter	16.0 mm

Motor

Motor type	Asynchronous motor

Environment Data

Protection class	I / Protective earthing
Degree of protection	IP65

Electrical System

Breaker Switch On/Off	no
Operating indicator	No
Adjusting frequency	No
Integrated transformer	No

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com