



## AP2560e

### Single direction vibratory plate

Soil and asphalt compaction without emissions

Wacker Neuson's AP2560e battery-operated vibratory plate offers a completely emission-free work site. This protects the operator and the environment. With its high speed and wide base plate, the AP2560e is ideal for compacting large areas. The base plate, made of heavy-duty nodular cast iron, and stable bearings contribute to the machine's long service life. With a battery runtime sufficient for a full day's work, the AP series offers the same performance as engine driven plates.

### Highlights

- Starts with a push of a button
- Maintenance-free electric motor
- No exhaust emissions
- Low energy costs
- Removable battery

### Technical Data

#### ■ Mechanical - Output Details

Centrifugal force	26 kN
Area capacity	756.0 m <sup>2</sup> /h
Forward Running	21.0 m/min
Gradeability	46.6 %
Standard Support Plate	without Support Plate

#### ■ Mechanical Details

Length Baseplate	650.0 mm
Width	600.0 mm
Width Baseplate	600.0 mm
Height	500.0 mm

Height Cover frame	500.0 mm
Thickness Baseplate	8.0 mm
Weight	133.00 kg
Ground clearance	500.0 mm

#### ■ Environment Data

Operating temperature range	0
HAV summation (average value)	4.4 m/s <sup>2</sup>
HAV summation (Standard)	EN 500-4

#### ■ Electrical System

Battery runtime	32.0 min
-----------------	----------