



PG2A Dewatering Pump

Efficiently extract clear water

With its self-priming centrifugal pumping action and overall compact size, the pump is ideal for the contractor with the need for temporary water removal.

Highlights

- Pump out vanes on back of impeller.
- Cast iron impeller and volute for long life and minimal service
- Carbon ceramic mechanical seal

Technical Data

Mechanical - Output Details

Flow rate max.	168.8 gal/mi
Solid diameter max.	0.3 "
Suction head max.	24.9 Foot
Delivery height max.	88.6 Foot

Mechanical Details

Length	18.9 "
Width	14.8 "
Height	15.6 "
Operating weight	55.1 lb
Intake-/Pressure socket-dia.	2.0 "

Engine

Cooling	• air cooling
---------	---------------

Engine type	• Gasoline engine
Engine operating mode	• four-stroke
Cylinder	1.0
Cylinder capacity	7.2 Inch ³
Fuel	• Gasoline
Fuel consumption	0.3 GPH US
Tank capacity	0.7 gal US
Oil filling max.	0.2 gal US
Power rating max.	3.5 hp
Engine speed (Power max.)	3,600.0 1/min
Standard (Operating power)	• SAE J1349
Engine Manufacturer	• Honda
Running time at 100%	1.9 hrs