

**NEW**



**KRAMER**  
*on the safe side*



**KL20.5T – MORE REACH, MORE EFFICIENCY**  
**READY FOR ANY CHALLENGE.**

# MACHINE HIGHLIGHTS AT A GLANCE

## THE KRAMER KL20.5T TELESCOPIC WHEEL LOADER

The KL20.5T is the perfect all-rounder that adapts to your work – powerful, robust and reliable in daily use. This makes it the ideal entry point into the world of telescopic wheel loaders. Its compact design combined with impressive performance makes it ideal for use in confined spaces – whether for stable work, feeding or bale handling. With its powerful 33 kW motor, a maximum speed of 30 km/h and an operating weight of over 3,000 kg, it offers the perfect balance of agility and stability.



### BENEFITS AT A GLANCE

- **Telescopic loading system** for greater reach, stacking and tipping height
- **Undivided vehicle frame** for stability, manoeuvrability and constant payload
- **Compact dimensions** ideal for confined spaces with a maximum width of 1.59 m
- **Two cab variants** for maximum compactness (low cab 2.11 m height) or maximum comfort (comfort cab 2.26 m height)
- **Versatile quick-change plates** such as Smart Attach for fast attachment changes



# REACH NEW HEIGHTS WITH THE TELESCOPIC LOADING SYSTEM

## MORE POSSIBILITIES

The KL20.5T from Kramer is a powerful telescopic wheel loader that sets new standards with its additional reach, stacking and dumping height. Thanks to the telescopic loading system, greater heights and distances can be handled effortlessly, safely and precisely. This ensures maximum versatility in use and sustainably increases productivity and cost-effectiveness.

**+39 % STACKING HEIGHT**

**+40 % LOAD-OVER HEIGHT**

**+50 % DUMPING HEIGHT**



### **POWERFUL Z-KINEMATICS**

Impresses with high load capacities at maximum reach and lift height

### **ROBUST CONSTRUCTION**

through the use of high-strength and torsionresistant box profiles

### **OPTIMAL VISIBILITY**

thanks to generously designed glass surfaces

### **MAXIMUM VERSATILITY**

through optional high-flow hydraulics



**KRAMER**  
*on the safe side*



WHEEL LOADER



TELESCOPIC WHEEL LOADER



TELEHANDLER



KA.EMEA.10423.V01.EN-GB

10/2025 EN-GB

## TECHNICAL DATA

### OPERATING AND POWER RATINGS

### KL20.5T

|                                |               |
|--------------------------------|---------------|
| Engine power [kW/hp]           | 33.3 / 45     |
| Bucket capacity [m³]           | 0.45 - 0.80   |
| Load-over height extended [mm] | 3,670         |
| Dumping height extended [mm]   | 3,170         |
| Stacking height extended [mm]  | 3,770         |
| Bucket tipping load [kg]       | 1,910         |
| Stacking payload S = 1.25 [kg] | 1,240         |
| Operating weight [kg]*         | 3,050 - 3,300 |

\*Weight with a full tank + standard bucket + 75 kg operator (ISO 6016 + weight varies depending on the equipment).

**Kramer-Werke GmbH**  
Wacker Neuson Straße 1  
88630 Pfullendorf  
Germany

info@kramer.de  
www.kramer.de



### SCAN NOW

Go to the Kramer  
dealer locator here

[www.kramer.de/dealerlocator](http://www.kramer.de/dealerlocator)