



HI1000

Indirect Fired Air Heaters

large air heater for the harshest applications

The HI1000 is Wacker Neuson's highest capacity indirect fired air heater. Available with or without a fuel tank. For remote applications, our DGM version includes a custom extended service genset. All versions are ETL certified.

Highlights

- Cold Weather Ready
- Digital control panel

Technical Data

■ Electrical - Output Details

Nominal current	30.00 A
Nominal voltage	230.0 V
Nominal frequency	60.0 Hz
Phase	1.0 ~

■ Mechanical Details

Length	3,034.0 mm
Width	1,186.0 mm
Height	1,707.0 mm
Lift Bail - quantity	1.0
Duct Length max., 3x12" Supply Adapter	30.0 m
Duct Length max., 2x16" Supply Adapter	30.0 m
Duct Length max., 1x20" Supply Adapter	61.0 m

Duct Length max., 1x20" Return Adapter	15.0 m
--	--------

■ Generator

Genset	no
--------	----

■ Environment Data

Sound level LpA	77.6 dB(A)
-----------------	------------

■ Electrical System

Temperature monitor	digital
---------------------	---------

■ Operating Fluids

Fuel Consumption Natural Gas	401.1 l/min
------------------------------	-------------

■ Shipping and Storage

Length for shipping	3,270.0 mm
Width for shipping	1,042.0 mm
Height for shipping	1,732.0 mm