





## AS62ve/25

## **Electric rammers**

Optimum adjustment of the impact rate to different soil conditions thanks to the speed adjustment.

The battery-powered rammer allows the operator to work completely free of emissions The battery-powered rammer is a win for soil compaction in trenches and inner cities as well as lightening the load for the operator and environment on every construction site. One battery charge is enough to finish all the tasks of an average workday. The battery can be easily changed without tools and can be used for a variety of other Wacker Neuson construction equipment.

## Highlights

- Speed adjustment
- Maintenance-free electric motor
- BatteryOne battery system
- Ergonomic guide handle
- Easy start
- Carry handle on the ramming shoe
- Active cooling
- No exhaust emissions

## **Technical Data**

Electrical - Output Details	
Nominal current	41.00 A
Nominal voltage	51.0 V
Nominal power [P]	2.10 KW
Mechanical - Output Details	
Number of blows	680.0 1/min
Area capacity	165.0 m2/h
Forward Running	11.0 m/min
Power of impact	17.0 kN
Mechanical Details	
Length	625.0 mm
Length Ramming Shoe	340.0 mm
Width	360.0 mm
Width Ramming Shoe	250.0 mm
Height	925.0 mm

Weight	59.00 kg
Operating weight	69.0 kg
Stroke at tamper	43.0 mm
Motor	
Motor type	Asynchronous motor
Environment Data	
Degree of protection	IP23D
Storage temperature range	-30 - 50 °C
Sound power LWA, guaranteed	108.0 dB(A)
Sound power LWA (Standard)	EN 500-4
HAV summation (average value)	7.7 m/s2
HAV summation (Standard)	EN 500-4
Operating Fluids	
Oil specification	SAE 10W-40
Oil volume	0.700 l

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.