



KL70.8

Wheel loader

The high-performance flagship

Extreme manoeuvrability, off-road capability and high efficiency characterise the Kramer wheel loader KL70.8. The excellent all-round visibility ensures safety and productivity while working and the ergonomically designed control panels add extra comfort. With numerous equipment options such as those for the loading system or several attachments, KL70.8 is perfectly suited for your requirements.

Hydraulics: Powerful working hydraulics with load sensing and a maximum of 180 l/min ensure the fastest possible working cycles

ecospeedPRO gearbox: A speed of up to 40 km/h with automatic speed regulation by the integrated Smart Driving

Traction: The switchable 100% differential lock in both axles is ideally suited for rough terrain

Engine: Powerful EU exhaust stage V Deutz engines with a maximum output of 115 kW (156 hp)

Intelligent: Automatic functions such as the automatic bucket return system or the automatic air conditioning system take the strain off the driver

Technical Data

Standard engine data

Engine manufacturer	Deutz
Drive output	115 kW
Drive output	156 PS
Cylinder capacity	4,038 cm ³
Exhaust standard level	V
Exhaust aftertreatment	DOC / DPF / SCR

Weights

Bucket capacity (standard bucket)	1.80 m ³
Payload (max.)	4,800 kg
Operating weight	11,050 - 11,220 kg
Payload (S=1.25)	4,800 kg
Payload (S=1.25 extended loader unit)	4,000 kg
Tipping load (standard bucket)	6,900 kg
Tipping load (pallet fork)	6,000 kg

Filling levels

Tank capacity for fuel	140 l
Tank capacity for hydraulic oil	125 l

Drive system

Travel speed Standard	0-20 km/h
Travel speed Option 1	0-30 km/h
Travel speed Option 2	0-40 km/h

Kinematics

Kinematics type	PZ
-----------------	----


Steering

Steering angle max.	40 degree
---------------------	-----------

Noise characteristic values

Guaranteed sound power level L _{WA} (cabin)	102 dB(A)
Measured sound power level L _{WA}	100.7 dB(A)
Sound pressure level at the operator's ear	70 dB(A)

Dimensions



A2	extended loading system	6,995 mm
A1	Total length with standard attachment	6,550 mm
B1	Wheel base center	2,620 mm
C1	Rear overhang	1,520 mm
D3	Height with cab	3,010 mm
D10	Total height with rotating beacon	3,175 mm
E1	Max. height blade pivot point	3,760 mm
E2	Max. height of hinge pin height extended loading system	4,200 mm
F1	Load-over height	3,520 mm
F2	extended loading system	3,950 mm
G1	Dumping height	2,695 mm
G2	extended loading system	3,210 mm
H1	Dumping width	1,172 mm
H2	extended loading system	1,300 mm
I1	Digging depth	150 mm
J1	Total width	2,500 mm
J2	Track width	1,955 mm
K1	Ground clearance	445 mm
L1	Turning radius outer edge wheels	3,865 mm
M1	Steering angle	40 °
M2	Swing angle	24 °
N1	Dumping angle at max. lifting height	45 °
O1	Dumping angle at ground level	41.5 °
P1	Distance center front axle to tooth tip	2,607 mm
Q1	Bucket width	2,500 mm
R1	Stacking height	3,605 mm
R2	extended loading system	4,055 mm

Standard components

Cab

- Comfortable, spacious cabin
- Interior lighting with door contact switch; entrance and exit on both sides
- Cabin inspected according to ROPS and FOPS; windshield wipers front and rear, front and back with intermittent wipers
- Telescoping and adjustable tilting steering column
- Joystick console (fold-down)
- Mechanically-sprung operator's seat (MSG85/722) with automatic seat belt; weight, back and twin horizontal adjustment
- 7" LCD display with integrated rear-view camera
- Electronically pilot-operated multifunction joystick with integrated travel direction selector for use at night
- 3-stage powerful heating and ventilation and defroster nozzles on the windscreen
- Bluetooth radio with hands-free system
- Automatic air conditioning
- 12 V socket
- Sun blind with three different positions
- Work lights 4x LED Basic (1000 Lumen)
- Lighting according to road traffic regulations

Steering and work hydraulics

- 3rd control circuit with proportional control and continuous function
- Pressure release of 3rd control circuit
- Oil volume for auxiliary control circuits can be set
- Floating position
- Automatic bucket retract mechanism
- Hydrostatic all-wheel steering with emergency steering properties

Engine

- Battery disconnect switch
- Hydraulic reversible fan
- Four-part cooling system (hydraulic, charge air, cooling water cooler, air conditioning condenser)
- Wide-opening engine hood with rubber seal, sight glass for hydraulic oil level and cooling water

Power transmission

- Combined brake-inch pedal
- 100% self-locking differential connectible in front and rear axle
- Electro-hydraulic disc brakes with spring suspension in the front axle, also acting on the rear axle via the universal joint shaft
- Pendulum pin lubrication line

Drive system & Axles

- Automotive infinitely variable hydrostatic axial piston transmission

Kinematics

- PZ-kinematics
- Hydraulic quickhitch facility according to ISO 23727 (Volvo TPV system)

Documentation

- Operator's manual, service manual

Options

Cab

- Rotating beacon (yellow)
- LED rotating beacon (yellow)
- Lighting package (8 work lights – 4 x front, 2 x rear, 2 x side) – omission of standard work lights
- LED lighting package (8 work lights – 4 x front, 2 x rear, 2 x side) – omission of standard work lights
- Air-sprung operator's seat with lumbar support (MSG95AL/722)
- Air-sprung operator's seat with lumbar support and heated seat (MSG95AL/722)
- Outside rear-view mirror electrically adjustable incl. mirror heating with automatic shut-off
- Carbon filter
- Bracket for cell phone
- Control console holder on B-pillar
- Document box
- Auxiliary heating, including engine pre-heater, programmable

Drive system & steering

- Ecospeed PRO 40 km/h incl. Smart Driving (throttling to 30 or 20 km/h possible ex works)
 - only in association with
 - Load stabilizer (vibration damper)
 - License plate illumination, including license plate bracket in front
- Low-speed device and hand throttle
- Accelerator pedal mode
 - only in association with
 - Low-speed device and hand throttle
- Ecospeed PRO 40 km/h incl. Smart Driving (throttled to 20 km/h)
 - only in association with
 - Load stabilizer (vibration damper)
 - License plate illumination, including license plate bracket in front
- Ecospeed PRO 40 km/h incl. Smart Driving (throttled to 30 km/h)
 - only in association with
 - Load stabilizer (vibration damper)
 - License plate illumination, including license plate bracket in front

Equipment for road traffic

- License plate illumination, including license plate bracket in front
- Data confirmation (ABE) for self-propelled working machine (standard) *
- EC certificate of conformity for tractor (167/2013/EC - class T1)
 - only in association with
 - License plate illumination, including license plate bracket in front
 - Outlet for rear attachments, 7-pole

In addition, a ball hitch (not a towing hitch) must be selected

* Germany, Luxembourg, Netherlands, Austria, Slovakia, Czech Republic, Switzerland, Estonia, Latvia, Lithuania, Hungary, Italy

Ball hitches & Brake systems

Recommended: EC Certificate of Conformity for tractors (167/2013/EC – Class T1)

In conjunction with an attachment coupling, a rear outlet must always be selected

- Automatic attachment coupling 38 mm – fixed to frame
- Bearing block for attachment couplings height-adjustable (insert required for attachment coupling height-adjustable)
- Automatic 38 mm attachment coupling insert for trailer mount height-adjustable
- Mechanical attachment coupling insert for trailer mount height-adjustable – 32 mm
- K50 ball hitch insert for trailer mount height-adjustable
- Dual-line air brake system
 - not with:
 - Hydrostatic 20 km/h incl. Smart Driving
- Hydraulic trailer brake valve
 - not with:
 - Hydrostatic 20 km/h incl. Smart Driving

Engine

- Engine Deutz TCD 4.1 115kW/156 hp with diesel particulate filter / emission standard: Stage V
- Engine pre-heating, fuel, hydraulic oil (230 V)

Quick change plates & Loading system

- Load stabilizer (vibration damper)
- Load stabilizer (vibration damper) – required with hose burst valve
- Industrial loader unit (technical data and available attachments may differ)
- Hydraulic quick coupler system, Kramer System HV/TH – L

*Due to the distance between the steering wheel and the front edge of the vehicle, driving with attachments on public roads is not permitted.

Hydraulics - General

- Filling the hydraulic system with environmentally friendly and biodegradable hydraulic oil

Hydraulics - front area

- Powerflow 150 l/min
 - only in association with
 - Unpressurized return line, front, including overflow oil line
- Powerflow 180 l/min including hydraulic pump with increased discharge volume 180 l/min
 - only in association with
 - Unpressurized return line, front, including overflow oil line
- 4. control circuit for front add-on equipment with 2nd hydraulic function, proportional
- Unpressurized return line, front, including overflow oil line
- Vibrating function tipping cylinder

Hydraulics - rear area

- Tipper connection
 - not with:
 - 2 double-acting rear ports
- Pressureless return line, rear
 - only in association with
 - 1 double-acting hydraulic connection at rear including tipper connection
- 2 double-acting connections at the rear
 - not with:
 - Tipper connection
 - 1 double-acting hydraulic connection at the rear including tipper connection
- 1 double-acting hydraulic connection at the rear including tipper connection
 - not with:
 - 2 double-acting rear connections

Electrical system

- Outlet for rear attachments, 7-pole
- Outlet for front add-on equipment, 7-pole (2 switch positions)
- Driving signal outlet 7-pin

Safety options

- Reverse alarm (acoustic)
- Immobilizer system, integrated in the ignition switch key
- Hose burst valve for lifting and tilting cylinders
- Red/white warning stripes (in accordance with DIN 30710)
- Triangular marking plate
- Winding protection for universal joint shaft
 - not with:
 - Powerflow 150 l/min
 - Powerflow 180 l/min including gear pump with increased discharge volume 180 l/min
- Protective measures against corrosive agents (salt and fertilizer)
- Fire extinguisher 2 kg
- Protection package Industry
 - includes:
 - Winding protection for universal joint shaft
 - Protective guard for front windshield, removable (not approved for public road use); rear protective guards; main front headlight protective guard
- Protective guard for front windshield, removable (not approved for public road use!)

Other

- Single-color RAL custom paint finish (gray parts not included)*
- (Fully automatic) central lubrication unit
- Reversible fan motor
- Central lubrication system (corrosive agents)
- Overseas transportation protection

* We reserve the right to decline paint finishes that exhibit similarities to protected colors or color combinations of other manufacturers!

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Tires

- Michelin 500/70R24 XMCL – traction profile
- Alliance 600/55-26.5 331 (restricted steering angle: 35°) – traction profile
 - Required:
 - Red/white warning stripes (in accordance with DIN 30710)
 - EC Certificate of Conformity for tractors (167/2013/EC – Class T1)
 - Outlet for rear attachments, 7-pole
 - Ball hitch
- Nokian 540/70R24 TRI – municipal profile
- Michelin 540/70R24 XMCL – traction profile
- Michelin 540/70R24 Bibload – multi-purpose profile
- Firestone 500/70 R24 164 A8 Duraforce UT
- Trelleborg 500/70R24 TH500 ET+40
- Trelleborg 500/70R24 TH400 ET+50

Extended warranties

- Security 24 (2000 h)
- Security 36 (3000 h)
- Security 48 (3000 h)
- Security 48 (4000 h)
- Security 48 (5000 h)
- Security 60 (4000 h)
- Security 60 (5000 h)