



## E3000

### Hydronic Heater

dual reeled hydronic heater for the toughest jobs.

Engineered for reliable performance and trouble-free starts for up to 140 hours of run time, the E3000 will provide maximum flow and ensure consistent heat delivery for thawing and curing applications. The E3000 thaws or cures up to 557 sq. m. With accessories this heater will cure up to 1672 sq. m. or provide 49703 sq. m. of dry heat at 83% efficiency, the highest in the industry.

### Highlights

- Powerful positive displacement pumps
- Dual hose reels

### Technical Data

#### ■ Electrical - Output Details

Nominal current	20.00 A
Nominal voltage	120.0 V

#### ■ Engine

Cooling	Water-cooling
Engine type	Diesel engine

#### ■ Mechanical Details

#### Cylinder

3.0
62.7 Inch3

Length	181.1 "
Gross Axle Weight Rating	5,079.5 lb

#### Cylinder capacity

Operating Engine speed	1,800.0 1/min
Engine Manufacturer	Kohler

Width	90.6 "
Height	94.5 "

#### ■ Environment Data

Operating temperature range	100 - 180 °F
■ Electrical System	

Height	94.5 "
Operating weight	9,032.3 lb

Temperature monitor	digital
Display Equipment	Performance monitoring light

Operating weight	9,032.3 lb
Dry Weight	7,557.5 lb

gross vehicular weight	9,032.3 lb
Lift Bail - quantity	1.0

length hose	2,998.7 Foot
■ Generator	

Oil volume	1.004 gal US
Fuel specification	Winter Blend Diesel No. 2

Insulation class	H
Output current 1~	30.0 A

Run Time (75 %)	108.0 hrs
Fuel Tank capacity	230.1 gal US

Output voltage	120.0 V
Output frequency	60.0 Hz

Utilizable tank capacity	221.9 gal US
Fuel Consumption no genset	2.7 GPH US

Output power	6.0 KW
Regulation [U] - Steady State	6.0 %

Fuel Consumption with genset	3.4 GPH US
Run Time (100 %)	81.0 hrs

Generator Manufacturer	Mecc Alte
Generator specification	Brushless with capacitor

Run Time (100 %)	81.0 hrs
■ Chassis	

Genset	yes
Brake	Electric brake

Tongue Weight, min.	846.6 lb
■ Electrical System	

Tongue Weight, max.	1,148.6 lb
Tires	225/75R15 D

## ■ Shipping and Storage

Shipping weight (with Trailer)	7,557.5 lb
--------------------------------	------------