



**WACKER
NEUSON**
all it takes!



PSTF2 400

Submersible Pump

Durable, lightweight and perfect for any job

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	200.0 l/min
Solid diameter max.	7.0 mm
Delivery height max.	12.0 m

■ Mechanical Details

Length	255.0 mm
Width	185.0 mm
Height	328.0 mm
Operating weight	11.3 kg
Intake-/Pressure socket-dia.	50.0 mm

■ Motor

Nominal power	0.40 KW
Nominal current	5.4 A
Nominal voltage	110.0 V

Nominal frequency	60.0 Hz
Nominal speed	3,321.0 1/min
Phase	1.0 ~

■ Environment Data

Temperature limit borrowed liquid	40.0 °C
-----------------------------------	---------

■ Electrical System

Length Cable	6.2 m
Cable cross-section	1.3 mm ²
Cable definition	PVC Sheath

■ Shipping and Storage

Length for shipping	410.0 mm
Width for shipping	255.0 mm
Height for shipping	217.0 mm
Shipping weight	16.6 kg