



PST3-750

Submersible Pump

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

The PST3 750 is capable of handling solids up to .4 inches, ideal for job sites needing fast dependable dewatering.

Highlights

- Variety of models
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

■ Electrical - Output Details

Nominal current	4.80 A
Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Phase	1.0 ~

■ Mechanical - Output Details

Flow rate max.	300.0 l/min
Solid diameter max.	7.0 mm
Delivery height max.	18.0 m

■ Mechanical Details

Length	285.0 mm
--------	----------

Width	184.0 mm
Height	389.0 mm
Operating weight	19.6 kg
Intake-/Pressure socket-dia.	80.0 mm

■ Motor

Nominal speed	2,820.0 1/min
---------------	---------------

■ Electrical System

Length Cable	10.0 m
Cable cross-section	1.0 mm ²