

PST3-750

Submersible Pump

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

The PST3 750 is capable of handling solids up to .4 inches, ideal for job sites needing fast dependable dewatering.

Highlights

- Variety of models
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Safe to run dry

Technical Data

Electrical - Output Details

Nominal current	4.80 A
Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Phase	1.0 ~

Mechanical - Output Details

Flow rate max.	300.0 l/min
Solid diameter max.	7.0 mm
Delivery height max.	18.0 m

Mechanical Details

Length	285.0 mm
Width	184.0 mm
Height	389.0 mm
Operating weight	19.6 kg
Intake-/Pressure socket-dia.	80.0 mm

Motor

Nominal speed	2,820.0 1/min

Electrical System

Length Cable	10.0 m
Cable cross-section	1.0 mm²

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com