



AR 43/3/230 v

External vibrators for consolidation of prefabricated concrete factories

Maximum reliability and safety

The AR43 external vibrator performs with maximum reliability and safety in the toughest operating conditions - even in 24-hour continuous applications. This is due to the low vibration and heat-resistant windings of the electric motor (plastic casing, Class H up to 180°C) as well as the extremely robust special bearings. It has a long service life and minimal maintenance requirements. Perfect for application with precast concrete elements.

Highlights

- Sturdy design

Technical Data

■ Electrical - Output Details

Nominal current	1.04 A
Nominal voltage	- 400.0
Nominal frequency	- 87.0
Nominal power [P]	- 0.50
Phase	3.0 ~

■ Mechanical - Output Details

Centrifugal force	- 10
Vibrations	- 5,220.0
Vibrations (Hz)	- 87.0
Centrifugal force max.	10.42 kN

■ Mechanical Details

Length	223.0 mm
Width	190.0 mm

Height	164.0 mm
Weight	8.75 kg
Unbalanced mass/side pos1	11.0
Unbalanced mass/side pos2	0.0

■ Motor

Motor type	Asynchronous motor
------------	--------------------

■ Environment Data

Protection class	I / Protective earthing
Degree of protection	IP67

■ Electrical System

Breaker Switch On/Off	no
Operating indicator	No
Adjusting frequency	No
Integrated transformer	No