



BPU 5545A US

Medium-weight reversible vibratory plates

Unbeatable on any surface

Highlights

- Sturdy and durable
- Very good accessibility to all maintenance points
- High surface performance

Technical Data

■ Mechanical - Output Details

Centrifugal force	12,364 lbf
Area capacity	9,170.9 ft ² /h
Forward Running	1.5 fps
Gradeability	36.4 %
Vibrations (Hz)	69.0 Hz

Height Cover frame 28.5 "

Thickness Baseplate 0.5 "

Operating weight 771.6 lb

Underclearance 28.5 - 33.8 "

■ Engine

Effective power 8.6 hp

Nominal Engine speed 2,600.0 1/min

■ Environment Data

HAV summation (average value) 8.2 ft/s²

HAV summation (Standard) EN 500-4

■ Mechanical Details

Length Baseplate	35.4 "
Width	23.8 "
Width Baseplate	17.3 "
Height	51.5 "

Available engines

Honda GX390-UT2X-QA-4-SD

Cylinder capacity	23.7 Inch3
Fuel consumption	0.5 GPH US
Tank capacity	1.6 gal US
Effective power	8.6 PS
Nominal Engine speed	3,000 1/min
Operating power	7.2 PS
Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Fuel	Gasoline
Standard (Effective power)	SAE J1349
Starter type	Recoil starter
Engine Manufacturer	Honda