



**WACKER
NEUSON**
all it takes!

PS2-2203

Submersible Pump

powerful and reliable for construction site dewatering

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

■ Electrical - Output Details

Nominal current	5.00 A
Nominal voltage	400.0 V
Nominal frequency	50.0 Hz
Phase	3.0 ~

■ Mechanical - Output Details

Flow rate max.	500.0 l/min
Solid diameter max.	8.5 mm
Delivery height max.	26.0 m

■ Mechanical Details

Length	235.0 mm
--------	----------

Width 215.0 mm

Height 570.0 mm

Operating weight 36.0 kg

Intake-/Pressure socket-dia. 50.0 mm

■ Motor

Nominal speed 2,860.0 1/min

■ Electrical System

Length Cable 20.0 m

Cable cross-section 1.5 mm²