



PSA2 800

Submersible Pump

Automatic, lightweight pumps, perfect for any task

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	81.9 gal/mi
Solid diameter max.	0.2 "
Delivery height max.	59.1 Foot

Nominal frequency 60.0 Hz

Nominal speed 3,300.0 1/min

■ Mechanical Details

Length	7.6 "
Width	8.8 "
Height	13.4 "
Operating weight	30.4 lb
Intake-/Pressure socket-dia.	2.0 "

■ Environment Data

Temperature limit borrowed liquid 104.0 - 32.0 °F

■ Electrical System

Length Cable	49.2 Foot
Cable cross-section	0.0 Inch ²
Cable definition	PVC Sheath

■ Shipping and Storage

Length for shipping	18.7 "
Width for shipping	10.5 "
Height for shipping	10.2 "
Shipping weight	37.4 lb

■ Motor

Nominal power	0.75 KW
Nominal current	5.3 A
Nominal voltage	220.0 V