



## PS3 1500

### Submersible Pump

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

#### Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

#### Technical Data

##### ■ Mechanical - Output Details

Flow rate max. 420.0 l/min

Solid diameter max. 8.5 mm

Delivery height max. 21.0 m

##### ■ Mechanical Details

Length 240.0 mm

Width 240.0 mm

Height 570.0 mm

Operating weight 28.8 kg

Intake-/Pressure socket-dia. 80.0 mm

##### ■ Motor

Nominal power 1.50 KW

Nominal current 11.5 A

Nominal voltage 220.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,440.0 1/min

##### ■ Environment Data

Temperature limit borrowed liquid 40.0 °C

##### ■ Electrical System

Length Cable 10.0 m

Cable cross-section 2.0 mm<sup>2</sup>

Cable definition PVC Sheath

##### ■ Shipping and Storage

Length for shipping 345.0 mm

Width for shipping 330.0 mm

Height for shipping 710.0 mm

Shipping weight 35.0 kg