


# FUE-M/S 75A 4CEE-32A

## Portable frequency converters

Light, sturdy and powerful

The frequency converters of the FUE series are distinguished by their light and compact design. Thanks to the aluminum design, they are easy to handle. With their high-quality electronics and the active cooling system, these machines deliver the highest output even in long-term application. The intelligent load and voltage management is particularly practical. It compensates for fluctuations of mains input voltage, incorrectly dimensioned extensions or appliances with greatly varying use of power.

## Highlights

- Intelligent load and voltage management

## Technical Data

### Electrical - Output Details

| | |
|---|---|
| Nominal current | 13.00 A |
| Nominal voltage | 400.0 - 415.0 V |
| Nominal frequency | 50.0 - 60.0 Hz |
| Output current | 75.0 A |
| Output voltage | 42.0 V |
| Output frequency | 200.0 Hz |
| Phase | 3.0 ~ |
| Output Phase | 3.0 ~ |

### Mechanical Details

| | |
|---|---|
| Length | 400.0 mm |
| Width | 250.0 mm |
| Height | 250.0 mm |
| Weight | 29.50 kg |

### Environment Data

| | |
|---|---|
| Protection class | I / Protective earthing |
| Degree of protection | IP44 |

### Electrical System

| | |
|---|---|
| Breaker Switch On/Off | Yes |
| Operating indicator | yes |
| Adjusting frequency | No |
| Length Cable | 2.5 m |
| Kind of plug | CEE-Plug 5P 16A 400V 6H |
| Receptacle Type | CEE 3P 32A 4H 50V 100-200Hz |
| Number of Sockets | 4.0 |

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.


Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com