



IRSEN58/042GV

High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSEN series of high-frequency internal vibrators offer a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN high-quality internal vibrators offer a variety of features and benefits.

Highlights

- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

Technical Data

Electrical - Output Details	
Nominal current	17.30 A
Nominal voltage	42.0 V
Nominal frequency	200.0 Hz
Nominal power [P]	1.05 KW
Phase	3.0 ~
■ Mechanical - Output Details	
Amplitude at air	2.500 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz
Mechanical Details	
Length Hose	0.8 m

Weight	14.50 kg
Rubber cap	yes
Motor	
Motor type	Asynchronous motor
Environment Data	
Protection class	III / Safety extra-low voltage
Degree of protection	IP67
Degree of protection Electrical System	IP67
	IP67 Yes
Electrical System	
Electrical System Breaker Switch On/Off	Yes

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes