



**WACKER  
NEUSON**  
*all it takes!*

## IRSEN58/042GV

### High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSEN series of high-frequency internal vibrators offer a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN high-quality internal vibrators offer a variety of features and benefits.

### Highlights

- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

### Technical Data

#### ■ Electrical - Output Details

Nominal current	17.30 A
Nominal voltage	42.0 V
Nominal frequency	200.0 Hz
Nominal power [P]	1.05 KW
Phase	3.0 ~

#### ■ Mechanical - Output Details

Amplitude at air	2.500 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

#### ■ Mechanical Details

Length Hose	0.8 m
-------------	-------

Weight	14.50 kg
Rubber cap	yes

#### ■ Motor

Motor type	Asynchronous motor
------------	--------------------

#### ■ Environment Data

Protection class	III / Safety extra-low voltage
Degree of protection	IP67

#### ■ Electrical System

Breaker Switch On/Off	Yes
Integrated transformer	No
Length Cable	15.0 m
Kind of plug	CEE-Plug 3P 32A 42V 4H