



BPU5260Ah

Medium-weight vibratory plates

Efficient and precise for trench and surface compaction

The medium-heavy, reversible vibratory plates offer the perfect combination of high forward and reverse speeds and outstanding compaction performance. They have been specially developed for the requirements of trench and surface compaction and enable efficient and precise compaction of different soil types and structures. With their modern and ergonomic user interface, they offer maximum convenience and make work easier, resulting in a noticeable increase in productivity. The diesel-powered Pro version also boasts a powerful machine control system with innovative features: Bluetooth connectivity via smartphone app, compaction control as standard and optional Compomatic and telematics functionality. Numerous machine diagnostics functions also simplify service and maintenance, ensuring smooth operation and a long service life for your machine.

Highlights

- Optimum control and ergonomics
- Low HAV ($< 2.5 \text{ m/s}^2$)
- Compomatic
- Digital machine control
- Easy cleaning due to open base plate

Technical Data

■ Mechanical - Output Details

Centrifugal force 11,690 lbf

Area capacity 7,890.0 ft²/h

Forward Running 1.4 fps

Vibrations (Hz) 69.0 Hz

■ Mechanical Details

Length Baseplate 38.0 "

Width 23.6 "

Width Baseplate 23.6 "

Height 57.0 "

Height Cover frame 32.2 "

Thickness Baseplate 0.6 "

Operating weight 822.3 lb

Underclearance 32.2 "

■ Engine

Effective power 11.7 hp

Nominal Engine speed 3,600.0 1/min

■ Environment Data

HAV summation (Standard) EN 500-4

Available engines

Honda GX390-UT2X-QA-4-SD

Cylinder capacity	23.7 Inch3
Fuel consumption	0.5 GPH US
Tank capacity	1.6 gal US
Effective power	8.6 PS
Nominal Engine speed	3,000 1/min
Operating power	7.2 PS
Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Fuel	Gasoline
Standard (Effective power)	SAE J1349
Starter type	Recoil starter
Engine Manufacturer	Honda