



## RD24-100c

### Tandem roller

Convenient and efficient

The RD24 is the compact, versatile roller for every construction site. With its three-point articulated pendulum joint, the roller achieves a consistently even weight distribution with optimum maneuverability and travel stability. As a result, excellent, high-quality asphalt surfaces can be achieved. The user benefits from intuitive operation as well as the comprehensive view of the compaction area. Because of its compact dimensions, the RD24 is an excellent choice for use in confined areas.

### Highlights

- Combination roller: Rear axle with rubber tires
- Uniform operating concept
- Large line-of-sight, compact construction

### Technical Data

#### ■ Mechanical - Output Details

Gradeability	30.0 %
Gradeability max. (without vibration)	40.0 %
Travel speed	0.0 - 6.0 m/H
Static linear load (front)	67.98 lb/in
Linear load with vibration Level I (front)	222.47 lb/in
Linear load with vibration Level II (front)	159.55 lb/in
Compaction force Level I (front)	8,768 lbf
Compaction force Level II (front)	6,295 lbf
Vibration frequency Level I (front)	65.0 Hz
Vibration frequency Level II (front)	51.0 Hz
Amplitude Level I (front)	0.0177 "
Amplitude Level II (front)	0.0177 "
Centrifugal force Level I (front)	7,419 lbf
Centrifugal force Level II (front)	4,496 lbf

Curb clearance left 2.2 "

Operating width 39.4 "

Turning radius inside 97.2 "

Operating weight with roll-over protective structure 5,258.0 lb

Wheelbase 66.9 "

Operating weight, max. 6,856.38 lb

Curb clearance (left) 22.4 "

Curb clearance (right) 22.4 "

Total height with ROPS 93.6 "

Empty weight with ROPS 4,828.1 lb

Turning radius outside 136.6 "

#### ■ Engine

Cylinder capacity	100.5 Inch <sup>3</sup>
Effective power	24.8 hp
Nominal Engine speed	2,200.0 1/min
Standard (Effective power)	ISO 14396
Starter battery Voltage	12.0 V
Battery capacity (nom. value)	70.0 Ah
Engine Manufacturer	Kubota
Engine Designation	D1703

#### ■ Environment Data

Sound level LpA	88.0 dB(A)
Sound power LWA, measured	104.0 dB(A)

Sound power LWA, guaranteed	106.0 dB(A)
Exhaust aftertreatment	no
Catalyst	no
Particle filter	no
CO (NRSC)	1.9 g/KWh
HC + NOx (NRSC)	5.9 g/KWh
PM (NRSC)	0.3 g/KWh

### ■ Operating Fluids

Water tank capacity	47.6 gal US
Fuel Tank capacity	11.1 gal US
<b>■ Chassis</b>	
Pendulum angle +/-	8.0 °
Width over tires (rear)	39.4 "
Number of tires (rear)	4.0
Wheel size (rear)	205/60-R16
Wheel load per tire (rear)	647.6 lb