



KRAMER
on the safe side



KT307

Telehandler

A compact all-rounder

The Kramer telehandler KT307 is a maneuverable all-round talent – compact dimensions combined with a stacking height of 7 meters and 3 tons of payload provide versatile operation in all agriculture applications. The powerful work hydraulics with load-sensing characteristics enables precise and intersecting movements, and ensures for a high level of productivity in the yard. A variable, hydrostatic drive system and cleverly designed maintenance access make daily application and maintenance a breeze.

Lift capacity: 3 t payload and 7 m stacking height

Engine: Economical in consumption and high torque (136 hp, exhaust emission stage V)

Loader unit: Complete bucket emptying, even when handling sticky materials with an overall pivot angle of over 150°

Engine bonnet design: Optimal visibility to the right thanks thanks to the flatly-designed engine bonnet

Safety: Smooth retraction and extension, and no undesired loss of materials as a result of the final position dampening

Technical Data

■ Standard engine data

Engine manufacturer	Deutz
Drive output	100 kW
Drive output	136 PS
at max. rpm	2,300 U/min
Cylinder capacity	3,621 cm ³
Exhaust aftertreatment	DOC / DPF / SCR

■ Weights

Payload (max.)	3,000 kg
Payload at max. reach	1,000 kg
Payload at max. stacking height	2,000 kg
Stacking height (max.)	7,000 mm
Payload max. (LSP 500 mm)	3,000 kg
Operating weight	5,921 - 7,250 kg
Thrust force (max.)	50 kN
Lift capacity (max.)	43 kN

■ Filling levels

Tank capacity for fuel	100 l
Tank capacity for hydraulic oil	100 l
Tank capacity for urea solution	9.5 l

■ Drive system

Travel speed Standard	0-30 km/h
Travel speed Option 1	0-20 km/h
Travel speed Option 2	0-40 km/h
Differential lock	100% connectible in the front axle (Option)

■ Hydraulic system

Work hydraulics discharge volume (max.)	100 l/min
---	-----------


■ Steering

Steering angle max.	38 degree
---------------------	-----------

■ Noise characteristic values

Guaranteed sound power level LwA (operator's canopy)	106 dB(A)
Measured sound power level LwA	105.1 dB(A)
Sound pressure level at the operator's ear	72 dB(A)

Dimensions



A1	Total length	4,880 mm
A2	Total length with bucket	5,600 mm
B1	Total width without bucket	2,285 mm
C1	Front track: rear	1,880 mm
D3	Total height of low cab	2,310 mm
E1	Cab width	990 mm
F1	Wheel base center	2,850 mm
G1	Ground clearance under axle and transmission, wading depth	415 mm
H1	Distance center rear wheel to rear	740 mm
I1	Rear approach angle (slope angle)	60 °
J1	Dumping angle	49 °
J2	Dumping angle	41 °
L1	Load-over height: retracted	4,520 mm
L2	Load-over height: extended	6,820 mm
M1	Dumping height: retracted	4,030 mm
M2	Dumping height: extended	6,330 mm
N1	Dumping width: extended	110 mm
O1	Tele extension length: retracted	5,255 mm
O2	Tele extension length: extended	7,820 mm
P1	Total height telescopic arm mounting in frame	1,600 mm
Q1	Distance center front wheel to bucket leading edge	1,920 mm
Q2	Distance center front wheel bearing quick change frame	1,290 mm
R1	Bucket pivot point: retracted	5,035 mm
R2	Bucket pivot point: extended	7,335 mm
S1	Turning radius outer edge wheels	3,840 mm
S2	Turning radius outer edge bucket	5,000 mm
T1	Entry height cab floor	720 mm
D4	Total height of high cab	2,490 mm
D5	Total height of low cab with rotating beacon	2,540 mm
D6	Total height of high cab with rotating beacon	2,720 mm
K1	Max. stacking height	7,000 mm