



PS2-3703

Submersible Pump

powerful and reliable for construction site dewatering

The robust PS series three-phase submersible pumps can handle wastewater containing solids up to a diameter of 20 mm. They feature a high flow rates and high heads, making them ideal for applications where it is important to dry out construction sites quickly and reliably. These high-quality pumps are extremely durable and easy to use. The PS series are also offered in lightweight aluminum models and automatic versions.

Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

	Electrical	-	Output	Details
--	------------	---	--------	---------

Nominal current	7.70 A			
Nominal voltage	400.0 V			
Nominal frequency	50.0 Hz			
Phase	3.0 ~			
Mechanical Details				
Mechanical Details				
Mechanical Details Length	235.0 mm			

Height	570.0 mm			
Operating weight	62.0 kg			
Intake-/Pressure socket-dia.	50.0 mm			
Motor				
Nominal speed	2,860.0 1/min			
■ Electrical System				
Length Cable	20.0 m			
Cable cross-section	1.5 mm2			

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.