

FUE6/042/200

Portable frequency converter

Light, sturdy and powerful

The frequency converter FUE6 is characterized by its light and compact design. Its aluminum body makes it very easy to handle. The high-quality electronics and the active cooling system ensure maximum performance even during continuous operation. Particularly practical is the intelligent voltage and performance management. It compensates for fluctuations of mains input voltage, incorrectly dimensioned extensions or appliances with greatly varying use of power.

Highlights

- Protective ground fault interrupter (GFI or GFCI)
- Intelligent load and voltage management

Technical Data

Electrical - Output Details

Nominal current	22.00 A
Nominal voltage	230.0 - 240.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [S]	5.20 kVA
Output current	52.0 A
Output voltage	42.0 V
Phase	1.0 ~
Output Phase	3.0 ~
Output Nominal power [S]	3.80 kVA

Mechanical Details

Length	20.5 in
Width	12.2 in
Height	19.4 in
Weight	65.04 lb

Environment Data

Protection class	I / Protective earthing
Degree of protection	IP44

Electrical System

Breaker Switch On/Off	Yes
Operating indicator	yes
Adjusting frequency	yes
Length Cable	32.8 Foot
Receptacle Type	CEE 3P 32A 4H 50V 100-200Hz
Number of Sockets	4.0

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com