



**WACKER  
NEUSON**  
*all it takes!*

## BS60-4AS 11IN US

### 4-stroke Rammers

Outstanding work performance and long service life

Wacker Neuson's four-stroke rammers are characterized by outstanding work performance. The large stroke, high ramming frequency, high impact energy and fast forward travel ensure first-class work results. Well thought-out functions also make the use of the four-stroke rammer even more user-friendly, extend its service life and reduce maintenance to a minimum.

### Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator

### Technical Data

#### ■ Mechanical - Output Details

Number of blows 656.0 1/min

Area capacity 148.0 m<sup>2</sup>/h

Forward Running 8.8 m/min

Power of impact 18.0 kN

#### ■ Mechanical Details

Length 673.0 mm

Length Ramming Shoe 340.0 mm

Width 343.0 mm

Width Ramming Shoe 280.0 mm

Height 965.0 mm

Weight 72.00 kg

Operating weight 72.0 kg

Stroke at tamper 81.0 mm

#### ■ Engine

Fuel consumption 1.0 L/hr

Oil filling max. 0.3 l

Operating power 2.7 KW

Operating Engine speed 4,100.0 1/min

Standard (Operating power) ISO 3046-1

#### ■ Environment Data

Operating temperature range -10 - 40 °C

Sound power LWA, guaranteed 108.0 dB(A)

Sound power LWA (Standard) EN 500-4

HAV summation (average value) 9.5 m/s<sup>2</sup>

HAV summation (Standard) EN 500-4

#### ■ Electrical System

Display Equipment Operating hours counter

Operating elements Pushbutton OFF

#### ■ Operating Fluids

Oil specification SAE 10W-40

Oil volume 0.900 l

Lubrication intervall 250.0 h