



**WACKER
NEUSON**
all it takes!

PS2-1503

Submersible Pump

powerful and reliable for construction site dewatering

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

■ Electrical - Output Details

Nominal current	3.50 A
Nominal voltage	400.0 V
Nominal frequency	50.0 Hz
Phase	3.0 ~

■ Mechanical - Output Details

Flow rate max.	430.0 l/min
Solid diameter max.	8.5 mm
Delivery height max.	21.5 m

■ Mechanical Details

Length	235.0 mm
--------	----------

Width	215.0 mm
-------	----------

Height	550.0 mm
--------	----------

Operating weight	35.0 kg
------------------	---------

Intake-/Pressure socket-dia.	50.0 mm
------------------------------	---------

■ Motor

Nominal speed	2,850.0 1/min
---------------	---------------

■ Electrical System

Length Cable	20.0 m
--------------	--------

Cable cross-section	1.5 mm ²
---------------------	---------------------