



E12540B

Hydronic Heater

easy to transport, simple to use hydronic heater.

The E 1250 was designed with the safety features you require and the simple, intelligent operation you desire. All operator interface points are conveniently located in the rear of the machine for simplified operation. Our new concrete cure mode simplifies the guesswork in maintaining proper concrete temperature, and our user-friendly control panel incorporates a watchdog circuit, E-Stop, and single point reset for the most common faults. All versions are telematics ready.

Highlights

- Powerful positive displacement pumps

Technical Data

■ Electrical - Output Details

Nominal current 15.00 A

Nominal voltage 120.0 V

Display Equipment

Performance monitoring light

■ Mechanical Details

Length 140.0 "

Gross Axle Weight Rating 3,999.2 lb

Width 76.0 "

Height 68.0 "

Operating weight 3,174.7 lb

Dry Weight 2,729.3 lb

gross vehicular weight 3,174.7 lb

Lift Bail - quantity 0.0

length hose 1,250.0 Foot

■ Operating Fluids

Fuel specification Winter Blend Diesel No. 2

Run Time (75 %) 90.0 hrs

Fuel Tank capacity 71.1 gal US

Utilizable tank capacity 68.2 gal US

Fuel Consumption no genset 1.0 GPH US

Fuel Consumption Natural Gas 17.5 gal/mi

Fuel Consumption Propane 1.5 GPH US

Run Time (100 %) 68.0 hrs

■ Chassis

Brake Electric brake

Hitch Type Centrifugal Clutch

Tongue Weight, min. 169.8 lb

Tongue Weight, max. 229.3 lb

Tires ST205/75R15

■ Generator

Genset no

■ Environment Data

Operating temperature range 100 - 199 °F

Sound level LpA 64.5 dB(A)

■ Shipping and Storage

Shipping weight 2,729.3 lb

Shipping weight (with Trailer) 2,729.3 lb

■ Electrical System

Temperature monitor digital