



RD24e-100c

Electric tandem roller

Comfortable, efficient, and emission-free

The RD24e has an electrically driven vibration and/or oscillation unit. As a result, compaction works can be performed emission-free without cutting corners in terms of performance. The three-point articulated joint ensures an equal weight distribution with optimal maneuverability and operational stability. The operator benefits from intuitive operation, as well as the extensive view of the compaction area. The compact dimensions make the RD24e an all-rounder for the construction site.

Highlights

- No exhaust emissions
- Uniform operating concept
- Large line-of-sight, compact construction

Technical Data

■ Mechanical - Output Details

| | |
|---------------------------------------|----------------|
| Gradeability | 30.0 % |
| Gradeability max. (without vibration) | 40.0 % |
| Travel speed | 0.0 - 8.0 km/h |
| Static linear load (front) | 130.40 kg/mm |
| Compaction force Level I (front) | 49 kN |
| Compaction force Level II (front) | 35 kN |
| Vibration frequency Level I (front) | 65.0 Hz |
| Vibration frequency Level II (front) | 51.0 Hz |
| Amplitude Level I (front) | 0.5000 mm |
| Amplitude Level II (front) | 0.5100 mm |
| Centrifugal force Level I (front) | 36 kN |

■ Mechanical Details

| | |
|------------------------|------------|
| Length | 2,530.0 mm |
| Width | 1,110.0 mm |
| Operating weight | 2,535.0 kg |
| Dry Weight | 2,360.0 kg |
| Gross vehicular weight | 2,640.0 kg |
| Curb clearance right | 55.0 mm |
| Curb clearance left | 55.0 mm |

| | |
|--|-------------|
| Operating width | 1,000.0 mm |
| Ground clearance | 280.0 mm |
| Turning radius inside | 2,470.0 mm |
| Operating weight with roll-over protective structure | 2,535.0 kg |
| Wheelbase | 1,700.0 mm |
| Operating weight, max. | 2,970.00 kg |
| Curb clearance (left) | 570.0 mm |
| Curb clearance (right) | 570.0 mm |
| Empty weight with ROPS | 2,360.0 kg |
| Turning radius outside | 3,470.0 mm |
| Drum width (front) | 1,000.0 mm |
| Drum diameter (front) | 720.0 mm |
| Drum thickness (front) | 15.0 mm |

■ Environment Data

| | |
|-----------------------------|-------------|
| Sound power LWA, measured | 99.0 dB(A) |
| Sound power LWA, guaranteed | 104.0 dB(A) |

■ Operating Fluids

| | |
|---------------------|---------|
| Water tank capacity | 180.0 l |
|---------------------|---------|

■ Chassis

| | |
|--------------------|-------|
| Pendulum angle +/- | 8.0 ° |
|--------------------|-------|