





BPS2050c

Single-direction vibratory plates

Easy to maneuver and high performance

These Wacker Neuson vibratory plates offer functionality and performance at a real value price. The compact design allows for compaction of mixed soils in the smallest spaces even in extremely narrow trenches. The guide handle with vibration damping results in longer working hours and less fatigue for the operator

Highlights

- Reliable Loncin engine
- Durable and maintenance free compaction system
- Big water tank
- Ergonomic and comfort designed handle
- Easy lifting and transport

Technical Data

Mechanical - Output Details

Centrifugal force	20 kN
Vibrations	5,460.0 - 5,700.0 1/min
Transmission	Centrifugal Clutch - V-belt
Area capacity	900.0 m2/h
Forward Running	25.0 - 30.0 m/min
Gradeability	30.0 %
Vibrations (Hz)	91.0 - 95.0 Hz
Mechanical Details	
Length Baseplate	615.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm
Height	880.0 mm
Thickness Baseplate	14.0 mm
Thickness Baseplate min.	11.0 mm

Operating weight	99.0 kg
Engine	
Effective power	4.4 KW
Nominal Engine speed	3,600.0 1/min
Environment Data	
Storage temperature range	-15 - 40 °C
Operating temperature range	-15 - 45 °C
Sound power LWA, guaranteed	108.0 dB(A)
Sound power LWA (Standard)	EN 500-4, 2000/14/EG
Vibration total value ahv	8.0 m/s2
Vibration value ahv (Standard)	EN 500-4
Operating Fluids	
Water tank capacity	10.0
Exciter oil volume	0.20
Fuel consumption	1.1 L/hr

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.