



PS2 500

Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

Highlights

- Top discharge for continuous operation and motor cooling
- Built-in thermal protection prevents motor damage
- Heavy-duty strain relief power cord
- Durable mechanical seals
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	62.3 gal/mi
Solid diameter max.	0.2 "
Delivery height max.	39.4 Foot

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

■ Mechanical Details

Length	7.3 "
Width	7.3 "
Height	12.0 "
Operating weight	20.9 lb

■ Electrical System

Length Cable 32.8 Foot

■ Motor

Nominal power	0.48 KW
---------------	---------

Length for shipping 13.7 "

Width for shipping 9.8 "

Height for shipping 9.0 "

Shipping weight 28.0 lb