



FUH70/6/42s

Portable frequency converters

Reliable performance at light weight

The FUH series offers compact, lightweight frequency converters for concrete processing with extremely reliable and stable performance, even in continuous operation. Thanks to the use of high-frequency technology, they are significantly lighter than electronic converters and therefore particularly convenient to transport. They are completely maintenance-free and are suitable for the operation of internal and external vibrators. The frequency adjustment allows an exact adaptation of the external vibrators to the respective formwork. The FUH can thus be used to produce perfect concrete surfaces.

Highlights

- Frequency adjustment
- Compact dimensions, low weight

Technical Data

■ Electrical - Output Details

Nominal current	16.00 A
Nominal voltage	230.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	3.70 KW
Output current	58.0 A
Output voltage	0.0 - 42.0 V
Output frequency	0.0 - 200.0 Hz
Phase	1.0 ~
Output Phase	3.0 ~
Output Nominal power [P - effective power]	0.0 - 3.4 KW

■ Mechanical Details

Length	598.0 mm
Width	303.0 mm

Height 562.0 mm

Weight 27.00 kg

■ Environment Data

Protection class II / Protective insulation

Degree of protection IP54

■ Electrical System

Breaker Switch On/Off Yes

Operating indicator yes

Adjusting frequency yes

Length Cable 2.2 m

Kind of plug CEE 7/17

Receptacle Type CEE 3P 32A 4H 50V 100-200Hz

Number of Sockets 6.0