



LTT6

Light Tower

Powerful and Compact

The LTT4 and LTT6 light towers offer a smaller footprint and the long-lasting LED's deliver exceptional light coverage for a variety of applications where temporary lighting is needed. The units are equipped with auxiliary power which adds to the versatility of these machines.

Highlights

- LED Lights
- Programmable Controller
- Compact Design
- Standard Auxiliary Power
- Telescopic Vertical Mast

Technical Data

■ Mechanical Details

Length	100.9 "
Width	47.5 "
Height	100.3 "
Operating weight	1,554.3 lb
Mast height max.	23.0 Foot

■ Generator

Output frequency	60.0 Hz
Voltage accuracy	10.0 %
Generator Rating 1~ (Continuous)	6.0 KW
Generator Manufacturer	Mecc Alte

■ Engine

Cooling	Water-cooling
Engine type	Diesel engine

Cylinder	3.0
Cylinder capacity	62.7 Inch ³
Fuel	Winter Blend Diesel No. 2
Tank capacity	52.4 gal US
Effective power	11.3 hp
Operating Engine speed	1,800.0 1/min
Exhaust-gas limit	EPA Tier 4 final
Engine Manufacturer	Kohler

■ Electrical System

Lighting appliances	320W (LED)
Bulb power	320.0 W

■ Operating Fluids

Fuel consumption (Lights only)	0.3 GPH US
Run Time (Lights only)	173.4 hrs