



## HI1000

### Indirect Fired Air Heaters

large air heater for the harshest applications

The HI1000 is Wacker Neuson's highest capacity indirect fired air heater. Available with or without a fuel tank. For remote applications, our DGM version includes a custom extended service genset. All versions are ETL certified.

### Highlights

- Cold Weather Ready
- Digital control panel

### Technical Data

#### ■ Electrical - Output Details

Nominal current	30.00 A
Nominal voltage	230.0 V
Nominal frequency	60.0 Hz
Phase	1.0 ~

#### ■ Mechanical Details

Length	3,034.0 mm
Width	1,186.0 mm
Height	2,088.0 mm
Operating weight	1,721.0 kg
Dry Weight	1,154.0 kg
Lift Bail - quantity	1.0
Duct Length max., 3x12" Supply Adapter	30.0 m
Duct Length max., 2x16" Supply Adapter	30.0 m
Duct Length max., 1x20" Supply Adapter	61.0 m
Duct Length max., 1x20" Return Adapter	15.0 m

#### ■ Generator

Genset	no
--------	----

#### ■ Environment Data

Sound level LpA	77.6 dB(A)
-----------------	------------

#### ■ Electrical System

Temperature monitor	digital
---------------------	---------

#### ■ Operating Fluids

Run Time (75 % Prime Load)	37.5 hrs
Fuel Tank capacity	719.2 l
Utilizable tank capacity	651.1 l
Fuel Consumption no genset	23.3 L/hr
Fuel Consumption with genset	24.2 L/hr
Run Time (100 %)	27.5 hrs

#### ■ Shipping and Storage

Length for shipping	3,270.0 mm
Width for shipping	1,042.0 mm
Height for shipping	2,113.0 mm