



IRFU65/120/5 US

High-frequency internal vibrators

Top Performance from every model

The IRFU high-frequency internal vibrator series are easy to use. They simply connect to the single-phase power supply and are ready to use. They offer reliable operation even when used with fluctuating generator input voltages. The Wacker Neuson IRFU high-performance internal vibrator is designed for long life and professional concrete consolidation results. It is available in many different versions. The integrated personal protection switch (Bodyguard™) offers a high standard of safety.

Highlights

- Bodyguard
- Bodyguard
- Completely tempered vibrator head
- Thermal overload protection breaker
- High-performance electric motor with stable speeds
- Switch box with integrated frequency converter

Technical Data

■ Electrical - Output Details

Nominal current	15.00 A
Nominal voltage	120.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	1.40 KW
Phase	1.0 ~

■ Mechanical - Output Details

Amplitude at air	0.098 "
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

■ Mechanical Details

Head diameter/-diagonal	2.6 "
-------------------------	-------

Length Hose	16.4 Foot
Weight	56.22 lb
Rubber cap	no

■ Environment Data

Protection class	I / Protective earthing
Degree of protection	IP67

■ Electrical System

Breaker Switch On/Off	Yes
Integrated transformer	yes
Length Cable	47.2 Foot
Kind of plug	NEMA 5-15P - 14W47